



MODEL 3010TA *Process Trace Oxygen Analyzer*

Teledyne's Model 3010TA Trace Oxygen Analyzer is a versatile microprocessor-based instrument for detecting oxygen at the parts-per-million (ppm) level in a variety of gases.

The 3010TA is designed as a "split architecture" instrument, meaning that a general purpose Control Unit for non-hazardous areas controls a specially designed Analysis Unit or "remote probe" that can operate in hazardous areas. Simple menu choices, membrane command switches and dual LCD and LED displays make set-up and operation clear and quick.

Three User-Configurable Analysis Ranges

Three user-configurable ranges are standard, with an excellent linearity precluding the need to recalibrate when changing ranges. Two fully programmable concentration alarms provide the versatility to satisfy nearly any requirement. All features offer a sophistication that assures the 3010TA will provide years of service.

Convenient Outputs For Data

Two standard 0-1 VDC outputs and two 4-20 mADC isolated outputs provide both concentration and range identification. A bi-directional RS-232 serial interface is incorporated to relay information to a host computer for remote monitoring of critical functions.

ADVANTAGES

- Linearity of analysis across three user-programmable ranges
- AutoRanging capabilities
- Digital interface allows monitoring from a remote station
- Extended-life, maintenance-free sensor
- Comprehensive self testing function

STANDARD FEATURES

- An explosion proof NEMA 4/7 rated analysis unit enclosure
- A 2-line alphanumeric display screen, driven by microprocessor electronics continuously prompting and informing the operator
- High resolution, accurate readings of oxygen content from low ppm levels through 25%
- Stainless steel cell block
- Advanced Micro-fuel Cell designed for trace analysis
- Versatile analysis over a wide range of applications
- Microprocessor based electronics: 8-bit CMOS microprocessor with 32kB RAM and 128kB ROM
- Three user-definable output ranges (from 0-10 ppm through 0-250,000 ppm) assuring a perfect match for the user's process and equipment
- Air-calibration range for convenient spanning at 20.9%
- Auto-Ranging automatically selects the proper preset range for a given measurement. Manual override allows the user to lock onto a specific range of interest.
- Two adjustable concentration alarms and a system failure alarm
- Extensive self-diagnostic testing at start-up and on demand with continuous power-supply monitoring
- Two way RS-232 serial digital port for use with a computer or other digital communication device
- Four analog outputs; two for measurement (0-1 VDC and Isolated 4-20 mADC) and two for range identification

APPLICATIONS

- Monitoring inert gas blanketing
- Air separation and liquefaction
- Chemical reaction monitoring
- Semiconductor manufacturing
- Petrochemical process control
- Quality assurance
- Gas analysis certification



MODEL 3010TA TRACE OXYGEN ANALYZER

SPECIFICATIONS:

Ranges:	3 customer programmable ranges (minimum 0-10 ppm) with AutoRanging	Sample connections:	1/4" with conversion to 6mm available
Calibration range:	0-25%	Area classifications:	Analysis unit: Explosion proof enclosure is U/L and CSA listed for Class I, Division 1, Groups B, C, D service NEMA 4/7 rated Control unit: General purpose flush panel mounted
Accuracy:	±1% of FS at a constant temperature	Dimensions:	6.96" H x 8.7" W x 12.2" L
Sensitivity:	0.5% of FS		
Response:	90% of FS at 77°F (25°C) in less than 65 seconds		
Operating temperature:	32°F to 122°F (0°C to 50°C)		
Signal output:	Analytical measurement: 0-1 VDC and 4-20 mADC (isolated)	Options	
Range ID output:	0-1 VDC and 4-20 mADC (isolated)	- C	Integrally mounted cal/zero valves
Analysis display:	5 digit red LED, 3/5" high numerals	- V	Plumbed for vacuum service
Menu display:	20 character, 2 line LCD	- F	Flame arrestors for Class I, Div 1, Group C/D service
Data lines:	Bi-directional RS-232C serial interface, baud rate 2400 - remote monitoring of all critical functions	- G	Flame arrestors for Class I, Div 1, Group C/D service with cal valves
Alarm:	One system failure alarm contact to detect power failure. Two fully programmable concentration alarm set points and corresponding form C 3 amp contacts.	- H	Flame arrestors for Group B (hydrogen) service
		- I	Flame arrestors for hydrogen service with cal valves
Power requirements:	Universal AC input ranges - Control unit: 85 / 230 VAC, 50-60 Hz Analysis unit: 115 / 230 VAC, 50-60 Hz	- K	19" rack mount available with either one or two analyzer Control Units installed and ready to mount in a standard rack.
Oxygen sensor:	Teledyne Micro-fuel Cell, Class L-2 (2 year life expectancy with most applications)		
Wetted parts:	316 stainless steel		

聯宙科技股份有限公司
Atlas Tech. Corp.
www.atlasgroup.com.tw

地址: 台灣新北市永和區保生路一號22樓
Add: 22F., No.1, Baosheng Rd., Yonghe
Dist., New Taipei City 23444, Taiwan

Tel: +886.2.2232.0556
Fax: +886.2.2231.6657
atlas@atlasgroup.com.tw

